

NON SAFETY CRITICAL

HEAVY DUTY NYLON ANCHOR

5mm - 6mm sizes

Stainless Steel Screw
External & marine applications


FEATURES & BENEFITS

- Through fastening, light duty.
- Set by hammering screw into nylon anchor body.
- Suitable for concrete, solid brick, block & stone.
- Removable with PH2 screwdriver if required.
- Nylon anchor body insulates anchor screw from fixture.


APPLICATIONS/TRADES

- Signage.
- Brackets.
- Fixing timber battens.


SUBSTRATE SUITABILITY



UNCRAKED
CONCRETE



SOLID BRICK



SOLID BLOCK



NATURAL
STONE



Countersunk head for a flush finish

Hammer in the screw to install

Nylon sleeve insulates the screw from the substrate

**STAINLESS
STEEL
316**

HEAVY DUTY NYLON ANCHOR

NON SAFETY CRITICAL

RANGE




COUNTERSUNK HEAD


Product Code	Pack Qty	Anchor / Drill hole Ø (mm)	Anchor length (mm)	Maximum fixture thickness (mm)	Drill hole depth (mm) @ $t_{fix, max}$	Minimum embedment depth @ $t_{fix, max}$	Fixture clearance hole Ø (mm)
		d_{nom}/d_o	l_t	$t_{fix, max}$	h_1	h_{nom}	d_f
ANHM6050332	100	5	33	8	30	25	6
ANHM6060552	100	6	55	25	30	30	7

Note: For a fixture thickness (t_{fix}) that is less than the $t_{fix, max}$ value tabled above:
 - increase both the drill hole depth (h_1) & concrete thickness (h_{min}) by ($t_{fix, max} - t_{fix}$ actual)


INSTALLATION




Drill hole into substrate to the specified diameter and depth



Clear hole of drilling debris.



Tap anchor through the fixture into the substrate until all are firmly in contact. Continue driving the screw until it is seated in the head of the anchor.



Screw may be removed later if required, using a screwdriver.

HEAVY DUTY NYLON ANCHOR

NON SAFETY CRITICAL

PRODUCT INSTALL & PERFORMANCE INFORMATION

Anchor / Drill hole Ø (mm)	Minimum embedment depth	Minimum substrate thickness	Phillips driver size	Recommended Capacities Load in any direction (kg)
d_{nom}/d_o	h_{nom}	h_{min}		F_{rec}
5	25	65	PH2	15
6	30	75	PH2	22

Note: Recommended capacities are based on:

- 20MPa concrete compressive strength.
- Characteristic ultimate capacities / 4.

Important Disclaimer: Capacity information is limited to the simple scope above and is provided to enable a relative comparison within and across product ranges. Please contact Bremick to enable an anchoring solution to be optimised for your particular anchoring application.