

HEX BOLT
CLASS 8.8 METRIC




APPLICATION

Bremick® Hex Head Metric Class 8.8 bolts are designed for industrial and construction applications where high tensile superior performance is required

PRODUCT ATTRIBUTES

Material Class:	Carbon Steel Class 8.8
Thread Form:	Metric 6g
Finish:	Zinc Plated
Standard:	Complies to AS 1110.1:2015 - Grade B
Mechanical Properties:	Complies to ISO 898.1:2013
Chemical Composition:	Complies to ISO 898.1:2013

HEAD MARKING



In some cases, the Bremick head mark will be replaced by the mark of the original manufacturer

MECHANICAL PROPERTIES

PROPERTIES	TENSILE STRENGTH (MPa)	STRESS UNDER PROOF LOAD (MPa)	HARDNESS					
	MIN	NOM.	VICKERS (HV)		BRINELL (HBW)		ROCKWELL (HRC)	
CLASS 8.8 ≤ M16	800	580	250	320	245	316	22	32
CLASS 8.8 >M16	830	600	255	335	250	331	23	34


CHEMICAL COMPOSITION (%)

MATERIAL	C		P	S	B	TEMPERING TEMPERATURE °C
	MIN	MAX	MAX	MAX	MAX	MIN
CARBON STEEL	0.25	0.55	0.025	0.025	0.003	425

FINISH INFORMATION

ZINC PLATED		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
Zinc Plating is a process of depositing a thin layer of zinc onto the surface of a steel object through electroplating. The steel object is then passivated with a transparent conversion layer.	Bremick® Zinc Plated Coating provides a low level of corrosion protection and is recommended for dry internal application. Bremick® Zinc Plating complies with AS1789.	Low.

DIMENSIONAL DATA (mm)



DIAMETER	PITCH (mm)	ACROSS FLATS (s)		ACROSS CORNERS (e)		HEAD HEIGHT (k)	
		MIN	MAX	MIN		MIN	MAX
M5	0.80	7.64	8.00	8.63		3.26	3.74
M6	1.00	9.64	10.00	10.89		3.76	4.24
M8	1.25	12.57	13.00	14.20		5.06	5.54
M10	1.50	15.57	16.00	17.59		6.11	6.69
M12	1.75	17.57	18.00	19.85		7.21	7.79
M14	2.00	20.16	20.67	22.78		8.51	9.09
M16	2.00	23.16	24.00	26.17		9.71	10.29
M20	2.50	29.16	30.00	23.95		12.15	12.895
M24	3.00	35.00	36.00	39.55		14.650	15.350
M27	3.00	40.00	41.00	45.20		13.65	17.35
M30	3.50	45.00	46.00	50.85		18.28	19.12
M36	4.00	53.80	55.00	60.79		22.08	22.92
M42	4.50	63.10	65.00	71.30		25.58	26.42
M48	5.00	73.10	75.00	82.60		29.58	30.42

SOCKET OR SPANNER SIZE (mm)

BOLT DIAMETER	M5	M6	M8	M10	M12	M14	M16	M20	M24	M27	M30	M36	M42	M48
SPANNER SIZE	8	10	13	16	18	21	24	30	36	41	46	55	65	75

THREAD LENGTH (mm)

LENGTH	M5	M6	M8	M10	M12	M14	M16	M20	M24	M27	M30	M36	M42	M48
20														
25														
30														
35														
40														
45														
50														
55	16													
60	16													
65	16	18												
70	16	18												
80	16	18												
90	16	18	22											
100	16	18	22											
110	16	18	22	26						60				
120	16	18	22	26						60	66			
130	22	24	28	32	36					66	72			
140	22	24	28	32	36					66	72	84		
150	22	24	28	32	36	40				66	72	84		
160		24	28	32	36	40	44	52	60	66	72	84	96	
180			28	32	36	40	44	52	60	66	72	84	96	108
200			28	32	36	40	44	52	60	66	72	84	96	108
220				45	49	53	57	65	73	79	85	97	109	121
240					49	53	57	65	73	79	85	97	109	121
260					49	53	57	65	73	79	85	97	109	121
280						53	57	65	73	79	85	97	109	121
300							57	65	73	79	85	97	109	121
320								65	73	79	85	97	109	121
340								65	73	79	85	97	109	121
360									73	79	85	97	109	121
380										79	85	97	109	121
400										-	85	97	109	121
420										-	-	97	109	121
440										-	-	97	109	121
460										-	-	97	109	121
480										-	-	-	109	121
500										-	-	-	109	121

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.
The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au