

SET SCREW CLASS 4.6 METRIC




APPLICATION

Bremick® Hex Head Metric Class 4.6 set screws are designed for industrial and construction applications where moderate tensile performance is required

PRODUCT ATTRIBUTES

Material Class:	Carbon Steel Class 4.6
Thread Form:	Metric 8g
Finish:	Zinc Plated
Standard:	Complies to DIN 933:1987
Mechanical Properties:	Complies to ISO 898.1:2013
Chemical Composition:	Complies to ISO 898.1:2013

HEAD MARKING



In some cases, the Bremick head mark will be replaced by the mark of the original manufacturer

MECHANICAL PROPERTIES

PROPERTIES	TENSILE STRENGTH (MPa)	STRESS UNDER PROOF LOAD (MPa)	HARDNESS					
	MIN	NOM.	VICKERS (HV)		BRINELL (HBW)		ROCKWELL (HRB)	
CLASS 4.6	400	225	120	220	114	209	67	95


CHEMICAL COMPOSITION (%)

MATERIAL	C		P	S	B	TEMPERING TEMPERATURE °C
	MIN	MAX	MAX	MAX	MAX	MIN
CARBON STEEL	-	0.55	0.050	0.060	Not Specified	-

FINISH INFORMATION

ZINC PLATED		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
Zinc Plating is a process of depositing a thin layer of zinc onto the surface of a steel object through electroplating. The steel object is then passivated with a transparent conversion layer.	Bremick® Zinc Plated Coating provides a low level of corrosion protection and is recommended for dry internal application. Bremick® Zinc Plating complies with AS1789.	Low.

DIMENSIONAL DATA (mm)



DIAMETER	PITCH (mm)	ACROSS FLATS (s)		ACROSS CORNERS (e)		HEAD HEIGHT (k)		MAJOR DIAMETER (d)	
		MIN	MAX	MIN		MIN	MAX	MIN	MAX
M3	0.50	5.32	5.50	6.01		1.88	2.12	2.86	3.00
M4	0.70	6.78	7.00	7.66		2.68	2.92	3.82	4.00
M5	0.80	7.78	8.00	8.79		3.35	3.65	4.82	5.00
M6	1.00	9.78	10.00	11.05		3.85	4.15	5.82	6.00
M8	1.25	12.73	13.00	14.38		5.15	5.45	7.78	8.00
M10	1.50	16.73	17.00	18.90		6.22	6.48	9.78	10.00
M12	1.75	18.67	19.00	21.10		7.32	7.50	11.73	12.00
M14	2.00	21.67	22.00	24.49		8.80	10.00	13.73	14.00
M16	2.00	23.67	24.00	26.75		9.82	10.18	15.73	16.00
M20	2.50	29.67	30.00	33.53		12.28	12.72	19.67	20.00
M24	3.00	35.38	36.00	39.98		14.78	15.22	23.67	24.00
M27	3.00	40.00	41.00	45.20		13.65	17.35	26.48	27.00
M30	3.50	45.00	46.00	50.85		18.28	19.12	29.48	30.00
M33	3.50	49.00	50.00	55.37		20.58	21.42	32.38	33.00
M36	4.00	53.80	55.00	60.79		22.08	22.92	35.38	36.00
M39	4.00	58.80	60.00	66.44		24.58	25.42	38.38	39.00

SOCKET OR SPANNER SIZE (mm)

BOLT DIAMETER	M3	M4	M5	M6	M8	M10	M12	M14	M16	M20	M24	M27	M30	M33	M36	M39
SPANNER SIZE	5.5	7	8	10	13	17	19	22	24	30	36	41	46	50	55	60

THREAD LENGTH

Thread length is equivalent to bolt length as set screws are fully threaded

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.
The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au