

SET SCREW A2-70 METRIC
STAINLESS STEEL



APPLICATION

Bremick® Set Screw Metric A2-70 Stainless Steel set screws are designed for industrial and construction applications where extreme corrosion performance is required


PRODUCT ATTRIBUTES

Material Class:	Stainless Steel A2-70
Thread Form:	Metric 6g
Standard:	Complies to DIN 933:1987
Mechanical Properties:	Complies to ISO 3506.1:2020
Chemical Composition:	Complies to ISO 3506.1:2020

HEAD MARKING

Manufacturer Mark

Property Class



In some cases, the Bremick head mark will be replaced by the mark of the original manufacturer

MECHANICAL PROPERTIES

PROPERTIES	TENSILE STRENGTH (MPa)	STRESS AT 0.2% NON-PROPORTIONAL ELONGATION (MPa)	ELONGATION AFTER FRACTURE
	MIN	MIN	MIN
CLASS 70	700	450	0.4d


CHEMICAL COMPOSITION (%)

STAINLESS STEEL GRADE	C	Si	Mn	P	S	Cr	Mo	Ni	Cu
	MAX	MAX	MAX	MAX	MAX	RANGE	RANGE	RANGE	MAX
A2	0.10	1.00	2.00	0.050	0.030	15.0-20.0	-	8.0-19.0	4.0

MATERIAL INFORMATION

STAINLESS STEEL 304		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
304 is the most commonly used stainless steel. It is an austenitic, offers excellent strength and corrosion resistance.	Bremick® 304 Stainless Steel provides an extreme level of protection and is recommended for wet external application. Bremick® 304 Stainless Steel is an austenitic stainless steel that offers all round performance.	Extreme

DIMENSIONAL DATA (mm)



DIAMETER	PITCH (mm)	ACROSS FLATS (s)		ACROSS CORNERS (e)		HEAD HEIGHT (k)		MAJOR DIAMETER (d)	
		MIN	MAX	MIN		MIN	MAX	MIN	MAX
M3	0.50	5.32	5.50	6.01		1.88	2.12	2.86	3.00
M4	0.70	6.78	7.00	7.66		2.68	2.92	3.82	4.00
M5	0.80	7.78	8.00	8.79		3.35	3.65	4.82	5.00
M6	1.00	9.78	10.00	11.05		3.85	4.15	5.82	6.00
M8	1.25	12.73	13.00	14.38		5.15	5.45	7.78	8.00
M10	1.50	16.73	17.00	18.90		6.22	6.48	9.78	10.00
M12	1.75	18.67	19.00	21.10		7.32	7.50	11.73	12.00
M14	2.00	21.67	22.00	24.49		8.80	10.00	13.73	14.00
M16	2.00	23.67	24.00	26.75		9.82	10.18	15.73	16.00
M20	2.50	29.67	30.00	33.53		12.28	12.72	19.67	20.00
M24	3.00	35.38	36.00	39.98		14.78	15.22	23.67	24.00
M27	3.00	40.00	41.00	45.20		13.65	17.35	26.48	27.00
M30	3.50	45.00	46.00	50.85		18.28	19.12	29.48	30.00
M33	3.50	49.00	50.00	55.37		20.58	21.42	32.38	33.00
M36	4.00	53.80	55.00	60.79		22.08	22.92	35.38	36.00
M39	4.00	58.80	60.00	66.44		24.58	25.42	38.38	39.00

SOCKET OR SPANNER SIZE (mm)

BOLT DIAMETER	M3	M4	M5	M6	M8	M10	M12	M14	M16	M20	M24	M27	M30	M33	M36	M39
SPANNER SIZE	5.5	7	8	10	13	17	19	22	24	30	36	41	46	50	55	60

THREAD LENGTH

Thread length is equivalent to bolt length as set screws are fully threaded

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.
The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au