

SOCKET COUNTERSUNK FLAT HEAD
 CAP SCREWS A2-70 METRIC
 STAINLESS STEEL



APPLICATION

Bremick® Flat Head (Counter Sunk) Socket Screws are high strength fasteners manufactured to precision tolerances for use in applications where close tolerances and high tensile strength is required. The heads of these fasteners are flat topped, counter sunk with an internal hex drive recess

PRODUCT ATTRIBUTES

Material Class:

Stainless Steel A2-70

Thread Form:

Metric 6g

Standard:

Complies to DIN 7991:1986

Mechanical Properties:

Complies to ISO 3506-1:2020

Chemical Composition:

Complies to ISO 3506-1:2020

HEAD MARKING

Manufacturer Mark

Property Class

In some cases, the Bremick head mark will be replaced by the mark of the original manufacturer

MECHANICAL PROPERTIES

PROPERTIES	TENSILE STRENGTH (MPa)	STRESS AT 0.2% NON-PROPORTIONAL ELONGATION (MPa)	ELONGATION AFTER FRACTURE
	MIN	MIN	MIN
CLASS 70	700	450	0.4d


CHEMICAL COMPOSITION (%)

STAINLESS STEEL GRADE	C	Si	Mn	P	S	Cr	Mo	Ni	Cu
	MAX	MAX	MAX	MAX	MAX	RANGE	RANGE	RANGE	MAX
A2	0.10	1.00	2.00	0.050	0.030	15.0-20.0	-	8.0-19.0	4.0

MATERIAL INFORMATION

STAINLESS STEEL 304		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
304 is the most commonly used stainless steel. It is an austenitic, offers excellent strength and corrosion resistance.	Bremick® 304 Stainless Steel provides an extreme level of protection and is recommended for wet external application. Bremick® 304 Stainless Steel is an austenitic stainless steel that offers all round performance.	Extreme

DIMENSIONAL DATA (mm)



DIAMETER	PITCH (mm)	COUNTERSUNK ANGLE (a)	SHAFT DIAMETER (ds)		HEAD DIAMETER (dk)		HEAD HEIGHT (k)	HEXAGON SOCKET SIZE ACROSS FLATS (s)		HEXAGON SOCKET SIZE ACROSS CORNERS (e)	KEY ENGAGEMENT (t)	
		NOM	MIN	MAX	MIN	MAX	MAX	MIN	MAX	MIN	MIN	MAX
M3	0.50	90°-92°	2.86	3.00	5.7	6.00	1.70	2.020	2.100	2.30	0.95	1.20
M4	0.70	90°-92°	3.82	4.00	7.64	8.00	2.30	2.520	2.600	2.87	1.55	1.80
M5	0.80	90°-92°	4.82	5.00	9.64	10.00	2.80	3.020	3.100	3.44	2.05	2.30
M6	1.00	90°-92°	5.82	6.00	11.57	12.00	3.30	4.020	4.120	4.58	2.25	2.50
M8	1.25	90°-92°	7.78	8.00	15.57	16.00	4.40	5.020	5.140	5.72	3.20	3.50
M10	1.50	90°-92°	9.78	10.00	19.48	20.00	5.50	6.020	6.140	6.86	4.10	4.40
M12	1.75	90°-92°	11.73	12.00	23.48	24.00	6.50	8.025	8.175	9.15	4.30	4.60
M14	2.00	90°-92°	13.73	14.00	26.48	27.00	7.00	10.025	10.175	11.43	4.50	4.80
M16	2.00	90°-92°	15.73	16.00	29.48	30.00	7.50	10.025	10.175	11.43	5.00	5.30
M18	2.50	90°-92°	17.73	18.00	32.38	33.00	8.00	12.032	12.212	13.72	5.20	5.50
M20	2.50	90°-92°	19.67	20.00	35.38	36.00	8.50	12.032	12.212	13.72	5.60	5.90
M22	2.50	60°-62°	21.67	22.00	35.38	36.00	13.10	14.032	14.212	16.00	8.44	8.80
M24	3.00	60°-62°	23.67	24.00	38.38	39.00	14.00	14.032	14.212	16.00	9.87	10.30

SOCKET OR SPANNER SIZE (mm)

SCREW DIAMETER	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24
SOCKET SIZE	2	2.5	3	4	5	6	8	10	10	12	12	14	14

THREAD LENGTH (mm)

NOMINAL LENGTH	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24
16	12	14											
20	12	14	16	18									
25	12	14	16	18	22								
30	12	14	16	18	22	26							
35	12	14	16	18	22	26	30	34					
40	12	14	16	18	22	26	30	34	38				
45	12	14	16	18	22	26	30	34	38	42			
50	12	14	16	18	22	26	30	34	38	42	46		
55	12	14	16	18	22	26	30	34	38	42	46	50	54
60	12	14	16	18	22	26	30	34	38	42	46	50	54
65	12	14	16	18	22	26	30	34	38	42	46	50	54
70	12	14	16	18	22	26	30	34	38	42	46	50	54
80	12	14	16	18	22	26	30	34	38	42	46	50	54
90	12	14	16	18	22	26	30	34	38	42	46	50	54
100	12	14	16	18	22	26	30	34	38	42	46	50	54
120	12	14	16	18	22	26	30	34	38	42	46	50	54
130	-	-	-	-	28	32	36	40	44	48	52	56	60
140	-	-	-	-	28	32	36	40	44	48	52	56	60
150	-	-	-	-	28	32	36	40	44	48	52	56	60
160	-	-	-	-	28	32	36	40	44	48	52	56	60
180	-	-	-	-	28	32	36	40	44	48	52	56	60
200	-	-	-	-	28	32	36	40	44	48	52	56	60
220	-	-	-	-	-	-	-	-	57	61	65	69	73
240	-	-	-	-	-	-	-	-	57	61	65	69	73
260	-	-	-	-	-	-	-	-	57	61	65	69	73
280	-	-	-	-	-	-	-	-	57	61	65	69	73
300	-	-	-	-	-	-	-	-	57	61	65	69	73

ALL SIZES ABOVE THE STEPPED LINE ARE FULLY THREADED

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.
The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au