

HEX NUT UNC F594D STAINLESS STEEL

APPLICATION

Bremick® Hex Nuts UNC 304 Stainless Steel are designed for industrial and construction applications where extreme corrosion performance is required

PRODUCT ATTRIBUTES


Material Class: 304 STAINLESS STEEL 1-CW2-F594D

Thread Form: Class 2B

Standard: Complies to ASME B18.2.2:2022

Mechanical Properties: Complies to ASTM F594:2024

Chemical Composition: Complies to ASTM F594:2024



MARKING



In some cases, the Bremick marking will be replaced by the mark of the original manufacturer

MECHANICAL PROPERTIES

ALLOY MECHANICAL PROPERTY MARKING	STRESS UNDER PROOF LOAD (ksi)	HARDNESS
		ROCKWELL
	MIN	RANGE
F594D	85	B80-C35


CHEMICAL COMPOSITION (%)

STAINLESS STEEL GRADE	C	Mn	P	S	Si	Cu	Ni	Cr
	MAX	MAX	MAX	MAX	MAX	MAX	RANGE	RANGE
304	0.08	2.00	0.045	0.030	1.00	1.00	8.0-10.5	18.0-20.0

MATERIAL INFORMATION

STAINLESS STEEL 304		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
304 is the most commonly used stainless steel. It is an austenitic, offers excellent strength and corrosion resistance.	Bremick® 304 Stainless Steel provides an extreme level of protection and is recommended for wet external application. Bremick® 304 Stainless Steel is an austenitic stainless steel that offers all round performance.	Extreme

DIMENSIONAL DATA (inches)



DIAMETER (inches)	TPI	ACROSS FLATS (s)		ACROSS CORNERS (e)		NUT HEIGHT (m)	
	UNC	MIN	MAX	MAX	MAX	MIN	MAX
3/4	10	1.088	1.125	1.240	1.299	0.617	0.665
7/8	9	1.269	1.312	1.447	1.516	0.724	0.776

SOCKET OR SPANNER SIZE (inches)

BOLT DIAMETER	3/4	7/8
SPANNER SIZE	1-1/8	1-5/16

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
 Head Office | 88 Dalmeny Avenue, Rosebery 2018
 National Distribution Centre | M5/M7 Logistics Park,
 Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au