

SOCKET COUNTERSUNK
FLAT HEAD CAP SCREWS
UNC



ZINC
PLATED

APPLICATION


Bremick® Flat Head (Counter Sunk) Socket Screws are high strength fasteners manufactured to precision tolerances for use in applications where close tolerances and high tensile strength is required. The heads of these fasteners are flat topped, counter sunk with an internal hex drive recess

PRODUCT ATTRIBUTES

Material Class:	Alloy Steel ASTM F835
Thread Form:	Class 3A UNRC $\leq 1"$ Class 2A UNRC $1" < x \leq 1\text{-}1/2"$
Finish:	Zinc Plated
Standard:	Complies to ASME B18.3:2012
Mechanical Properties:	Complies to ASTM F835:2023
Chemical Composition:	Complies to ASTM F835:2023

HEAD MARKING

Manufacturer Mark



In some cases, the Bremick head mark will be replaced by the mark of the original manufacturer

MECHANICAL PROPERTIES (Full-Size Tests)

DIAMETER (inches)	TENSILE STRENGTH (ksi)	HARDNESS			
		ROCKWELL (HRC)		VICKERS (DPH)	
NOMINAL	MIN	MIN	MAX	MIN	MAX
$\leq 0.5"$	144	39	44	382	434
$> 0.5"$	136	37	44	363	434


CHEMICAL COMPOSITION (%)

ANALYSIS	C		P	S
	MIN	MAX	MAX	MAX
HEAT	0.30	0.48	0.035	0.040
PRODUCT	0.28	0.50	0.040	0.045

FINISH INFORMATION

ZINC PLATED		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
Zinc Plating is a process of depositing a thin layer of zinc onto the surface of a steel object through electroplating. The steel object is then passivated with a transparent conversion layer.	Bremick® Zinc Plated Coating provides a low level of corrosion protection and is recommended for dry internal application. Bremick® Zinc Plating complies with AS1789.	Low.

DIMENSIONAL DATA (inches)



DIAMETER	TPI	BODY DIAMETER (ds)		HEAD DIAMETER (dk)		HEAD HEIGHT (k)	HEXAGON SOCKET SIZE (s)	KEY ENGAGEMENT (t)	COUNTERSUNK ANGLE (a)	
		MIN	MAX	MIN	MAX	REFERENCE	NOMINAL	MIN	MIN	MAX
6#	32	0.1329	0.1380	0.263	0.307	0.097	0.078	0.066	80°	84°
10#	24	0.1840	0.1900	0.359	0.411	0.127	0.125	0.087	80°	84°
1/4	20	0.2435	0.2500	0.480	0.531	0.161	0.156	0.111	80°	84°
5/16	18	0.3053	0.3125	0.600	0.656	0.198	0.188	0.135	80°	84°
3/8	16	0.3678	0.3750	0.720	0.781	0.234	0.219	0.159	80°	84°
7/16	14	0.4294	0.4375	0.781	0.844	0.234	0.250	0.159	80°	84°
1/2	13	0.4919	0.5000	0.872	0.938	0.251	0.312	0.172	80°	84°
5/8	11	0.6163	0.6250	1.112	1.188	0.324	0.375	0.220	80°	84°
3/4	10	0.7406	0.7500	1.355	1.438	0.396	0.500	0.220	80°	84°
7/8	9	0.8647	0.8750	1.604	1.688	0.468	0.562	0.248	80°	84°
1	8	0.9886	1.0000	1.841	1.938	0.540	0.625	0.297	80°	84°
1-1/8	7	1.1086	1.1250	2.079	2.188	0.611	0.750	0.325	80°	84°
1-1/4	7	1.2336	1.2500	2.316	2.438	0.683	0.875	0.358	80°	84°
1-3/8	6	1.3568	1.3750	2.553	2.688	0.755	0.875	0.402	80°	84°
1-1/2	6	1.4818	1.5000	2.791	2.938	0.827	1.000	0.435	80°	84°

Head Height: Tabulated values for head height are given for reference only and are calculated to the maximum formulation

SOCKET OR SPANNER SIZE (inches)

SCREW DIAMETER	6#	10#	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1	1-1/8	1-1/4	1-3/8	1-1/2
SOCKET SIZE	5/64	1/8	5/32	3/16	7/32	1/4	5/16	3/8	1/2	9/16	5/8	3/4	7/8	7/8	1

THREAD LENGTH (inches)

NOMINAL LENGTH	6#	10#	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
0.88											
1											
1.25	0.75										
1.5		0.88									
1.75	0.75	1.13	1								
2	1	0.88	1.25	1.12							
2.25	0.75	1.13	1	1.37	1.25						
2.5	1	0.88	1.25	1.12	1.5	1.38	1.5				
2.75	0.75	1.13	1	1.37	1.25	1.63	1.75				
3	-	0.88	1.25	1.12	1.5	1.38	2				
3.25	-	1.13	1	1.37	1.25	1.63	1.5	1.75			
3.5	-	0.88	1.25	1.12	1.5	1.38	1.75	2			
3.75	-	1.13	1	1.37	1.25	1.63	2	2.25	2		
4	-	0.88	1.25	1.12	1.5	1.38	1.5	1.75	2.5	2.5	
4.25	-		1	1.37	1.25	1.63	1.75	2	2.75	2.75	2.5
4.5	-	-	1.25	1.12	1.5	1.38	2	2.25	2	3	3
4.75	-	-	1	1.37	1.25	1.63	1.5	1.75	2.25	2.25	3.25
5	-	-	1.25	1.12	1.5	1.38	1.75	2	2.5	2.5	2.5
5.25	-	-	1	1.37	1.25	1.63	2	2.25	2.75	2.75	2.75
5.5	-	-	-	1.12	1.5	1.38	1.5	1.75	2	3	3
5.75	-	-	-	1.37	1.25	1.63	1.75	2	2.25	2.25	3.25
6	-	-	-	1.12	1.5	1.38	2	2.25	2.5	2.5	2.5
6.25	-	-	-	1.37	1.25	1.63	1.5	1.75	2.75	2.75	2.75
6.5	-	-	-	1.12	1.5	1.38	1.75	2	2	3	3
6.75	-	-	-	-	1.25	1.63	2	2.25	2.25	2.25	3.25
7	-	-	-	-	1.5	1.38	1.5	1.75	2.5	2.5	2.5
7.25	-	-	-	-	1.25	1.63	1.75	2	2.75	2.75	2.75
7.5	-	-	-	-	1.5	1.38	2	2.25	2	3	3
7.75	-	-	-	-	1.25	1.63	1.5	1.75	2.25	2.25	3.25
8	-	-	-	-	-	1.38	1.75	2	2.5	2.5	2.5
8.5	-	-	-	-	-	1.38	1.5	1.75	2	3	3
9	-	-	-	-	-	1.38	2	2.25	2.5	2.25	2.5
9.5	-	-	-	-	-	1.38	1.5	1.75	2	2.75	3
10	-	-	-	-	-	-	2	2.25	2.5	2.25	2.5
11	-	-	-	-	-	-	-	1.75	2	2.25	2.5
12	-	-	-	-	-	-	-	1.75	2	2.25	2.5
13	-	-	-	-	-	-	-	-	2	2.25	2.5
14	-	-	-	-	-	-	-	-	2	2.25	2.5
15	-	-	-	-	-	-	-	-	2	2.25	2.5
16	-	-	-	-	-	-	-	-	-	2.25	2.5
17	-	-	-	-	-	-	-	-	-	2.25	2.5
18	-	-	-	-	-	-	-	-	-	2.25	2.5
19	-	-	-	-	-	-	-	-	-	-	2.5
20	-	-	-	-	-	-	-	-	-	-	2.5

**ALL SIZES ABOVE THE STEPPED LINE
ARE FULLY THREADED**

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.
The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au