

MACHINE SCREW IMPERIAL CSK PHILIPS STAINLESS STEEL



STAINLESS
STEEL
304

APPLICATION

Bremick® Used in a variety of application they are designed for use in a pre-tapped hole or with a nut. The countersunk head provides a flush finish to avoid interference with other components.

PRODUCT ATTRIBUTES

Material Class: Stainless Steel 304

Thread Form: Free Class BSW

Standard: Complies to BS 450:1958

Chemical Composition: Complies to ISO 3506-1:2020


CHEMICAL COMPOSITION (%)

STAINLESS STEEL GRADE	C	Si	Mn	P	S	Cr	Mo	Ni	Cu
	MAX	MAX	MAX	MAX	MAX	RANGE	RANGE	RANGE	MAX
A2	0.10	1.00	2.00	0.050	0.030	15.0-20.0	-	8.0-19.0	4.0

MATERIAL INFORMATION

STAINLESS STEEL 304		
DESCRIPTION	OVERVIEW	CORROSION RESISTANCE
304 is the most commonly used stainless steel. It is an austenitic, offers excellent strength and corrosion resistance.	Bremick® 304 Stainless Steel provides an extreme level of protection and is recommended for wet external application. Bremick® 304 Stainless Steel is an austenitic stainless steel that offers all round performance.	Extreme

DIMENSIONAL DATA (inches)



SCREW SIZE (inches)	BASIC DIAMETER (d)	TPI	HEAD DIAMETER (dk)		HEAD HEIGHT (k)
			MIN	MAX	MAX
3/16	0.1875	24	0.307	0.328	0.084
1/4	0.2500	20	0.412	0.438	0.113

DRIVER SIZE (inches)

SCREW DIAMETER	3/16	1/4
PHILIPS DRIVE SIZE	2	3

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
 Head Office | 88 Dalmeny Avenue, Rosebery 2018
 National Distribution Centre | M5/M7 Logistics Park,
 Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au