

TIGHTENING TORQUE

STAINLESS STEEL METRIC THREADED RODS

RECOMMENDED TIGHTENING TORQUE (Nm)				
DIAMETER	PITCH (mm)	CLASS 50	CLASS 70	CLASS 80
M3	0.50	0.413	0.885	1.178
M3.5	0.60	0.651	1.388	1.852
M4	0.70	0.962	2.059	2.740
M5	0.80	1.937	4.154	5.332
M6	1.00	3.299	7.067	9.422
M7	1.00	5.524	11.82	15.76
M8	1.25	7.998	17.14	22.85
M10	1.50	15.83	33.93	45.24
M12	1.75	27.72	59.16	78.87
M14	2.00	44.14	94.55	126.1
M16	2.00	68.45	146.7	195.5
M18	2.50	94.58	202.7	270.3
M20	2.50	133.7	286.5	381.9
M22	2.50	182.2	390.7	520.8
M24	3.00	231.0	495.1	660.2
M27	3.00	338.6	725.9	967.7
M30	3.50	459.4	984.0	1312
M33	3.50	625.1	1339	1785
M36	4.00	803.1	1720	2294
M39	4.00	1039	2226	2968

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.
The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au