

10-24 HEX HEAD SDM



**ZINC
YELLOW**


APPLICATION

Bremick® 10-24 Hex Head SDM screw is for internal use, fixing metal-to-metal.

PRODUCT ATTRIBUTES



BF Hex Drive provides traceability and offers greater engagement and hex socket stability.



Finish Yellow Zinc Enhanced Corrosion Protection defends against rust, prolonging product life and provides a yellow-to-gold rainbow iridescence finish.

SDM Point for drilling into steel while ensuring maximum pullout strength and a high strip torque.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Metal Battens G550
- Steel Purlins G450

Max drilling capacity of 4.0mm.

When fastening metal, ensure 3 threads minimum embedment, protrude below battens / purlins.

INSTALLATION INSTRUCTIONS

1. Use a 5/16" Bremick® Hex Socket.
2. Insert the socket into a Power tool and select a drive speed of 3,000 RPM maximum.
3. Fit the screw into the socket and place the tip of the screw at the fastening position.
4. Apply firm pressure, drive until the screw has fastened. Do NOT overdrive.

10-24 HEX HEAD SDM

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
10-24	6.3	11.1	8.3

PULL OUT VALUES


Mean Ultimate Pull Out Force kN – Steel Purlins

SIZE	1.0mm BMT G450	1.2mm BMT G450	1.5mm BMT G450	1.9mm BMT G450	2.4mm BMT G450	3.0mm BMT G300	4.0mm BMT G300
10-24	2.8	3.0	4.3	5.2	6.7	7.2	9.8

Mean Ultimate Pull Out Force kN – Metal Battens

SIZE	0.42mm BMT G550	0.55mm BMT G450	0.55mm BMT G550	0.75mm BMT G550	0.9mm BMT G550	1.0mm BMT G550	1.2mm BMT G550
10-24	0.9	0.9	1.0	1.8	2.1	2.2	2.6

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products.
 The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
SMHFZ100162	SDM 10-24x16 HEX	5/16" Hex	1,000	ZINC YELLOW	16	9.8

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd

Head Office | 88 Dalmeny Avenue, Rosebery 2018
 National Distribution Centre | M5/M7 Logistics Park,
 Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170

www.bremick.com.au