

14-10 HEX HEAD TYPE 17 SS304

APPLICATION


Bremick® 14-10 Hex Head Type 17 SS304 screw is designed for crest fixing roof sheets, insulated roof and side panels to timber and thin metal top hat battens in cyclonic regions. This product is available either bare or with EDPM Sealing Washer.

In cyclonic regions the 14-10 Type17 can be used with the Region D® Plate or the BRA® Washer.



STAINLESS
STEEL
304

PRODUCT ATTRIBUTES



BF A2 Hex Drive provides traceability and offers greater engagement and hex socket stability.

Finish Stainless Steel 304 suitable for Category CX corrosive environments in accordance with ISO 9223-2012 and AS4312-2019.

Type 17 Point for drilling into timber while ensuring maximum pullout strength and a high strip torque.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Timber (JD3 min).
- Metal Battens 0.75mm BMT G550 min.

When fastening to timber, ensure a minimum thread embedment of 25mm.

When fastening metal, ensure 3 threads minimum embedment, protrude below battens / purlins.

In cyclonic regions, consult design professionals for fastener spacing.

INSTALLATION INSTRUCTIONS

1. Use a 3/8" Bremick® Hex Socket.
2. Insert the socket into a Power tool and select a drive speed of 1000 to 1500 RPM.
3. Fit the screw into the socket and position the screw point on the crest of the Rib.
4. Commence drilling at "slow speed" to pierce sheeting.
5. Apply firm pressure, drive until the seal seats firmly. Do NOT overdrive. Reverse screw if washer or roof sheet is deformed from over driving.

14-10 HEX HEAD TYPE 17 SS304

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
14-10	7.2	12.4	11.9

PULL OUT VALUES


Mean Ultimate Pull Out in F5/JD4 Timber (Radiata Pine)

SIZE	20mm Embedment	25mm Embedment	30mm Embedment	35mm Embedment	40mm Embedment
14-10	3.9	5.4	6.0	6.3	6.9

Mean Ultimate Pull Out in F17/J3 Timber (Hardwood)

SIZE	20mm Embedment	25mm Embedment	30mm Embedment	35mm Embedment	40mm Embedment
14-10	4.1	6.6	7.1	8.2	9.0

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products. The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
STHC5140502	T17 14-10x50 HEX	3/8" Hex	1000	SS304	50	35
STHC5140501	T17 14-10x50 HEX +SL	3/8" Hex	1000	SS304	50	35
STHC5140651	T17 14-10x65 HEX +SL	3/8" Hex	1000	SS304	65	40
STHC5140752	T17 14-10x75 HEX	3/8" Hex	500	SS304	75	50
STHC5140751	T17 14-10x75 HEX +SL	3/8" Hex	500	SS304	75	50

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application. The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au