

M6.2-13 HEX HEAD VORTEX CYCLONIC™




APPLICATION

Bremick® M6.2-13 Hex Head Vortex Cyclonic™ screw is designed for crest fixing roof sheets to top hat and timber battens.

The M6.2-13 Hex Head Vortex Cyclonic™ is used with the BRA Washer and is suitable for cyclonic regions.

**REVOLUTIONARY
PROTECTION &
PERFORMANCE**
for corrosive environments

PRODUCT ATTRIBUTES



B8V Hex Head provides traceability and offers greater engagement and hex socket stability.

BRA Washer designed by Bremick® and certified for cyclonic applications.

Top Grip provides a positive seal and reduces the roof sheet riding down.

Finish high corrosion performance with the B8® Coating. Suitable for Category 5 corrosive environments in accordance with ISO 9223-2012 and AS4312-2008.

Vortex® Point for faster starting, no skidding and stable installation.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Timber (JD3 min).
- Metal Battens 0.55mm BMT G550 min.
- Steel Purlins 1.5mm BMT G450 max.

When fastening to timber, ensure a minimum thread embedment of 25mm.

When fastening metal, ensure 3 thread minimum embedment, protrude below battens / purlins. In cyclonic regions, consult design professionals for fastener spacing.

INSTALLATION INSTRUCTIONS

1. Use a 3/8" Bremick® Hex Socket.
2. Insert the socket into a Power tool and select a drive speed of 1000 to 1500 RPM.
3. Fit the screw into the socket and position the screw point on the crest of the Rib.
4. Commence drilling at "slow speed" to pierce sheeting.
5. Apply firm pressure, drive until the seal seats firmly. Do NOT overdrive. Reverse screw if washer or roof sheet is deformed from over driving.

M6.2-13 HEX HEAD VORTEX CYCLONIC™

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
M6.2-13	11.0	16.7	14.1

PULL OUT VALUES

Mean Ultimate Pull Out Force kN – Steel Purlins

SIZE	1.0mm BMT G450	1.2mm BMT G450	1.5mm BMT G450	1.9mm BMT G450
M6.2-13	3.5	4.9	5.4	8.0

Mean Ultimate Pull Out Force kN – Metal Battens

SIZE	0.42mm BMT G550	0.55mm BMT G450	0.55mm BMT G550	0.75mm BMT G550	0.9mm BMT G550	1.0mm BMT G550	1.2mm BMT G550
M6.2-13	1.5	1.5	2.0	2.5	3.1	3.5	4.9


Mean Ultimate Pull Out in F5/JD4 Timber (Radiata Pine)

SIZE	25mm Embedment	30mm Embedment	35mm Embedment
M6.2-13	3.1	4.7	6.2

Mean Ultimate Pull Out in F17/J3 Timber (Hardwood)

SIZE	25mm Embedment	30mm Embedment	35mm Embedment
M6.2-13	4.6	6.2	6.5

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products. The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
SUHC862055D	SDMT HEX B8(Cat5) 6.2-13x55 BRA	3/8" Hex	250	B8® COATING	55	30
SUHC862065D	SDMT HEX B8(Cat5) 6.2-13x65 BRA	3/8" Hex	250	B8® COATING	65	40

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au