

14-10 HEX HEAD SDM CYCLONIC™




**REVOLUTIONARY
PROTECTION &
PERFORMANCE**
for corrosive environments

APPLICATION

Bremick® 14-10 Hex Head SDM Cyclonic™ screw is designed for crest pierce fixing roof and side cladding to steel purlins.

The 14-10 Hex Head SDM Cyclonic™ can be used with either the Region D cyclone plate or the BRA® Washer.

PRODUCT ATTRIBUTES




B8® Hex Drive provides traceability and offers greater engagement and hex socket stability.



Finish BRA washer designed by Bremick and certified for cyclonic applications

Finish High Corrosion performance with the B8® Coating. Suitable for Category 5 corrosive environments in accordance with ISO 9223-2012 and AS4312-2008.



SDM Point for drilling into steel while ensuring maximum pullout strength and a high strip torque.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Metal Battens G550
- Steel Purlins G450

Max drilling capacity of 5.0mm.

When fastening metal, ensure 3 threads minimum embedment, protrude below battens / purlins.

INSTALLATION INSTRUCTIONS

1. Use a 3/8" Bremick® Hex Socket.
2. Insert the socket into a Power tool and select a drive speed of 1000 to 1500 RPM.
3. Fit the screw into the socket and position the screw point on the crest of the Rib.
4. Commence drilling at "slow speed" to pierce sheeting.
5. Apply firm pressure, drive until the seal seats firmly. Do NOT overdrive. Reverse screw if washer or roof sheet is deformed from over driving.

14-10 HEX HEAD SDM CYCLONIC™

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
14-10	11.1	20.3	20.8

PULL OUT VALUES

Mean Ultimate Pull Out Force kN – Steel Purlins


SIZE	1.0mm BMT G450	1.2mm BMT G450	1.5mm BMT G450	1.9mm BMT G450	2.4mm BMT G450	3.0mm BMT G300	4.0mm BMT G300
14-10	3.0	3.7	4.6	6.4	8.4	9.8	12.0

Mean Ultimate Pull Out Force kN – Metal Battens

SIZE	0.42mm BMT G550	0.55mm BMT G450	0.55mm BMT G550	0.75mm BMT G550	0.9mm BMT G550	1.0mm BMT G550	1.2mm BMT G550
14-10	1.1	1.1	1.1	1.8	2.1	2.5	2.7

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products.

The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
SMHC814050D	SDM 14-10x55 HEX +BRA	3/8" Hex	250	B8® COATING	55	40
SMHC814055R	SDM 14-10x55 HEX +REGION "D"	3/8" Hex	250	B8® COATING	55	40

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd

Head Office | 88 Dalmeny Avenue, Rosebery 2018
 National Distribution Centre | M5/M7 Logistics Park,
 Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170

www.bremick.com.au