

10-16 WAFER HEAD SDM

APPLICATION

Bremick® Wafer Head SDM Screw can be used for the assembly of steel wall frames, wall bracing, door and window lintels.

The product does not require a pre punched hole but can be used with pre punched holes Ø4.1mm or smaller. Other applications are fixing Concealed Fix Clips and Side Cladding.




REVOLUTIONARY PROTECTION & PERFORMANCE
for corrosive environments

PRODUCT ATTRIBUTES



B8® Wafer Head low profile head for secret fix cladding.



Colormatch can be painted to match Colorbond® sheeting products.

Finish High Corrosion performance with the B8® Coating. Suitable for category 5 corrosive environments as described in ISO 9223-2012 and AS4312-2008.

SDM Point for drilling into steel while ensuring maximum pullout strength and a high strip torque.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Metal Battens G550
- Steel Purlins G450

Max drilling capacity of 4.0mm.

When fastening metal, ensure 3 threads minimum embedment, protrude below battens / purlins.

INSTALLATION INSTRUCTIONS

1. Use a Bremick® Phillips No.2 drive bit.
2. Insert the drive bit into a Power tool and select a drive speed of 3,000 RPM maximum.
3. Fit the screw into the socket and place the tip of the screw at the fastening position.
4. Apply firm pressure, drive until the screw has fastened. Do NOT overdrive.

10-16 WAFER HEAD SDM

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
10-16	6.3	11.1	8.3

PULL OUT VALUES


Mean Ultimate Pull Out Force kN – Steel Purlins

SIZE	1.0mm BMT G450	1.2mm BMT G450	1.5mm BMT G450	1.9mm BMT G450	2.4mm BMT G450	3.0mm BMT G300	4.0mm BMT G300
10-16	2.8	3.0	4.3	5.2	6.7	7.2	9.8

Mean Ultimate Pull Out Force kN – Metal Battens

SIZE	0.42mm BMT G550	0.55mm BMT G450	0.55mm BMT G550	0.75mm BMT G550	0.9mm BMT G550	1.0mm BMT G550	1.2mm BMT G550
10-16	0.9	0.9	1.0	1.8	2.1	2.2	2.6

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products.
The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
SMWC8100162	SDM 10-16x16 WAFER B8(Cat5)	PHILLIPS DRIVE No.2	1,000	B8® COATING	16	9.8
SMWC8100168	SDM 10-16x16 WAFER B8(Cat5)	PHILLIPS DRIVE No.2	100	B8® COATING	16	9.8
SMWC8100228	SDM 10-16x22 WAFER B8(Cat5)	PHILLIPS DRIVE No.2	100	B8® COATING	22	15.8

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd

Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170

www.bremick.com.au