

M6.2-14 HEX HEAD VORTEX POLY™




**REVOLUTIONARY
PROTECTION &
PERFORMANCE**
for corrosive environments

APPLICATION

Bremick® M6.2-14 Hex Head Vortex® POLY™ screw is designed for crest pierce fixing polycarbonate roof sheets to top hat and timber battens.

Typical applications are pergolas, outdoor entertainment areas and skylights.

PRODUCT ATTRIBUTES



B8® Hex Head provides traceability and offers greater engagement and hex socket stability.

Polycarb seal for a watertight seal.

Wing to create an expansion hole in the polycarbonate roof sheet.

Finish high corrosion performance with the B8® Coating. Suitable for Category 5 corrosive environments in accordance with ISO 9223-2012 and AS4312-2008.

Vortex® Point with **thread-to-point technology** for faster starting, no skidding and stable installation.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Timber (JD3 min).
- Metal Battens 0.75mm BMT G550 min.
- Steel Purlins 1.5mm BMT G450 max.

When fastening to timber, ensure a minimum thread embedment of 25mm.

When fastening metal, ensure 3 threads minimum embedment, protrude below battens / purlins.

In cyclonic regions, consult design professionals for fastener spacing.

INSTALLATION INSTRUCTIONS

1. Use a 5/16" Bremick® Hex Socket.
2. Insert the socket into a Power tool and select a drive speed of 1000 to 1500 RPM.
3. Fit the screw into the socket and position the screw point on the crest of the Rib.
4. Commence drilling at "slow speed" to pierce sheeting.
5. Apply firm pressure, drive until the seal seats firmly. Do NOT overdrive. Reverse screw if washer or roof sheet is deformed from over driving.

M6.2-14 HEX HEAD VORTEX POLY™

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
M6.2-14	11.0	16.7	14.1

PULL OUT VALUES

Mean Ultimate Pull Out Force kN – Steel Purlins

SIZE	1.0mm BMT G450	1.2mm BMT G450	1.5mm BMT G450	1.9mm BMT G450
M6.2-14	3.5	4.9	5.4	8.0

Mean Ultimate Pull Out Force kN – Metal Battens

SIZE	0.42mm BMT G550	0.55mm BMT G450	0.55mm BMT G550	0.75mm BMT G550	0.9mm BMT G550	1.0mm BMT G550	1.2mm BMT G550
M6.2-14	1.5	1.5	2.0	2.5	3.1	3.5	4.9


Mean Ultimate Pull Out in F5/JD4 Timber (Radiata Pine)

SIZE	25mm Embedment	30mm Embedment	35mm Embedment
M6.2-14	3.1	4.7	6.2

Mean Ultimate Pull Out in F17/J3 Timber (Hardwood)

SIZE	25mm Embedment	30mm Embedment	35mm Embedment
M6.2-14	3.8	4.7	6.2

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products. The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)
SUHT862050P	VORTEX POLY 6.2-14x50 HEX	5/16" Hex	250	B8® COATING	50	26.5
SVHEXC862050PT	VORTEX POLY 6.2-14x50 HEX	5/16" Hex	100	B8® COATING	50	26.5
TUHT862050P	VORTEX POLY 6.2-14x50 HEX	5/16" Hex	100	B8® COATING	50	26.5
SVHEXC862065PT	VORTEX POLY 6.2-14x65 HEX	5/16" Hex	100	B8® COATING	65	41.5
SUHT862065P	VORTEX POLY 6.2-14x65 HEX	5/16" Hex	250	B8® COATING	65	41.5
TUHT862065P	VORTEX POLY 6.2-14x65 HEX	5/16" Hex	100	B8® COATING	65	41.5

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd
Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170
www.bremick.com.au