

14-6 BUGLE BATTEN B8® FASTEN STRONG™

TORX⁺
40
Drive



**REVOLUTIONARY
PROTECTION &
PERFORMANCE**
for corrosive environments




APPLICATION

Bremick® 14-6 Bugle Batten B8® Coating Fasten Strong™ screw designed for fastening heavy timber to timbers.

Used for fixing timber Decking, Framing, Pergolas, Landscaping, Retaining Walls, Fencing and Gates, Furniture construction.

PRODUCT ATTRIBUTES



T40 Torx Drive Positive bit engagement allowing for maximum torque to be applied.

Ribbed Bugle Head Assists with embedment, to provide a secure flush finish.

Clearing Thread Pulls material together tightly and removes debris for a cleaner finish.

Finish high corrosion with the B8® Coating. Suitable for Category 5 corrosive environments in accordance with ISO 9223-2012 and AS4312:2019.

Serrated Sharp Thread Provides an aggressive cutting action, dramatically decreasing installation time.

Straight Cutter Reduces driving torque for faster installation.

DRILLING & INSTALLATION CAPACITY

Base Materials:

- Timber (JD3 min).
- Hardwood (F17 max).

When fastening to timber, ensure a minimum thread embedment of 35mm.

INSTALLATION INSTRUCTIONS

1. Use Bremick® T40 Drive bit.
2. Insert the socket into a power tool and select a drive speed of 3,000 RPM maximum for softwood or 1000RPM maximum for hardwood.
3. Fit the screw into the socket and place the tip of the screw at the fastening position.
4. Apply firm pressure, drive until the screw has fastened. Do NOT overdrive.

14-6 BUGLE BATTEN B8® FASTEN STRONG™

MECHANICAL PROPERTIES

SIZE	Single Shear (kN)	Axial Tensile (kN)	Torsional (Nm)
14-6	11.1	20.3	20.8

PULL OUT VALUES



Mean Ultimate Pull Out in F5/JD4 Timber (Radiata Pine)

SIZE	35mm Embedment	55mm Embedment
14-6	5.3	9.2

Mean Ultimate Pull Out in F17/J3 Timber (Hardwood)

SIZE	35mm Embedment	55mm Embedment
14-6	8.2	TBD

Note: The above data represents characteristic capabilities obtained under laboratory conditions and are only applicable to Bremick products. The design professional must apply appropriate safety factors.



RANGE

Product Code	Description	Head Driver	Pack Qty (EA)	Finish	Length L (mm)	Thread Length TL (mm)	AUS	NZ
SOBBTC8140502M	Fasten Strong™ Bugle Batten	T40 Torx Drive	25	B8® COATING	50	35	●	●
SOBBTC8140502T	Fasten Strong™ Bugle Batten	T40 Torx Drive	100	B8® COATING	50	35	●	●
SOBBTC8140502I	Fasten Strong™ Bugle Batten	T40 Torx Drive	500	B8® COATING	50	35	●	
SOBBTC8140752M	Fasten Strong™ Bugle Batten	T40 Torx Drive	25	B8® COATING	75	50	●	●
SOBBTC8140752T	Fasten Strong™ Bugle Batten	T40 Torx Drive	100	B8® COATING	75	50	●	●
SOBBTC8140752K	Fasten Strong™ Bugle Batten	T40 Torx Drive	250	B8® COATING	75	50		●
SOBBTC8140752I	Fasten Strong™ Bugle Batten	T40 Torx Drive	500	B8® COATING	75	50	●	
SOBBTC8140852M	Fasten Strong™ Bugle Batten	T40 Torx Drive	25	B8® COATING	85	55		●
SOBBTC8140852T	Fasten Strong™ Bugle Batten	T40 Torx Drive	100	B8® COATING	85	55		●
SOBBTC8141002M	Fasten Strong™ Bugle Batten	T40 Torx Drive	25	B8® COATING	100	65	●	●
SOBBTC8141002T	Fasten Strong™ Bugle Batten	T40 Torx Drive	100	B8® COATING	100	65	●	●
SOBBTC8141002K	Fasten Strong™ Bugle Batten	T40 Torx Drive	250	B8® COATING	100	65		●
SOBBTC8141002I	Fasten Strong™ Bugle Batten	T40 Torx Drive	500	B8® COATING	100	65	●	●
SOBBTC8141252M	Fasten Strong™ Bugle Batten	T40 Torx Drive	25	B8® COATING	125	75	●	●
SOBBTC8141252T	Fasten Strong™ Bugle Batten	T40 Torx Drive	100	B8® COATING	125	75	●	●
SOBBTC8141252K	Fasten Strong™ Bugle Batten	T40 Torx Drive	250	B8® COATING	125	75	●	●
SOBBTC8141502M	Fasten Strong™ Bugle Batten	T40 Torx Drive	25	B8® COATING	150	100	●	●
SOBBTC8141502T	Fasten Strong™ Bugle Batten	T40 Torx Drive	100	B8® COATING	150	100	●	●
SOBBTC8141502K	Fasten Strong™ Bugle Batten	T40 Torx Drive	250	B8® COATING	150	100	●	●

† Torx is a registered trademark owned by Acument Intellectual Properties, LLC

Whilst every care was taken in the preparation of this publication, Bremick® accepts no responsibility for the accuracy of the information supplied. Bremick® reserves the right to make alterations to specifications as part of ongoing development and improvement. This publication serves as a guide and it's the responsibility of the end user to ensure suitability for their application.

The contents of this publication are the exclusive copyright of Bremick® and may not be reproduced without permission.

BREMICK®

Bremick Pty Ltd

Head Office | 88 Dalmeny Avenue, Rosebery 2018

National Distribution Centre | M5/M7 Logistics Park,

Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170

www.bremick.com.au